



BRUSHBUSTER BT

STEEL GOOSENECK BAR TOP STOCK TRAILER WITH HIGH BRUSH FENDERS.

AVAILABLE SIZES

- 16' x 6'-8" x 6'6" w/ 2-5200# axles, 15" radial tires & 6-hole wheels
- 16' x 6'-8" x 6'6" w/ 2-6000# axles, 16" radial tires & 8-hole wheels
- 20' x 6'-8" x 6'6" w/ 2-6000# axles, 16" radial tires & 8-hole wheels
- 20' x 6'-8" x 6'6" w/ 2-7000# axles, 16" radial tires & 8-hole wheels
- 24' x 6'-8" x 6'6" w/ 2-7000# axles, 16" radial tires & 8-hole wheels
- 24' x 6'-8" x 6'6" w/ 2-8000# Torflex axles, 16" radial tires & 8-hole wheels
- 28' x 6'-8" x 6'6" w/ 3-6000# axles, 16" radial tires & 8-hole wheels
- 28' x 6'-8" x 6'6" w/ 3-7000# axles, 16" radial tires & 8-hole wheels
- 32' x 6'-8" x 6'6" w/ 3-7000# axles, 16" radial tires & 8-hole wheels
- 28' x 6'-8" x 6'6" w/ 2-8000# axles, 16" radial tires & 8-hole wheels

DIMENSIONS

- 7' gooseneck length
- 6'8" width
- 6'6" standard height

UNDERCARRIAGE

- Spring axles w/greasable hubs
- Forward self adjusting electric brakes on all wheels
- Radial Tires on silver modular wheels w/ chrome center caps
- Spare tire rack on GN

COUPLER AND JACKS

- Adjustable stem w/ set screw & pin w/ 2-5/16" coupler & safety chains w/ hooks
- Emergency breakaway system: switch, cable & battery box complete w/ battery & charger
- 12K Single speed drop-leg jack

DESIGN FEATURES AND HARDWARE

- Heavy duty gooseneck structure w/ 8" box channel upright
- All steel frame w/ 1"x 3" tubing sides
- 1" pipe runners on side above tubing sides and on roof
- 1 5/8" formed steel wall post and roof crossmember
- 4' channel cross member on 48" centers
- 6" front nose bonnet radius formed of 1" pipe steel
- 10 gauge steel formed high brush fenders
- Pin striping
- 2"x8" treated wood floor
- Greasable exterior hinges
- Tag bracket
- 12 step automotive grade paint process
- 1 5/8" Steel pipe bumper

LOAD AREA EQUIPMENT

- Heavy duty anti climb center gate w/ hold back & spring loaded slam latch (24' & 28' lengths have 2; 32' has 3) made of 1" pipe steel on 3" centers (interior and exterior latch release)
- Heavy Duty double swing in & out butterfly rear gates w/vertical and horizontal latching system

LIGHTS AND ELECTRICAL

- DOT required lighting

CM Trailers reserves the right to make any change in paint, design, or construction as necessary for engineering. All visual representation, specification, and dimensions are based on the latest product information available at the time of publication. Some of the equipment shown or described is available at extra cost. At no time will any of the material or information contained in this publication have any justifications for resolving disputes. All axle ratings will be listed as per FMVSS 120, Section 5.1 states, the maximum load rating of the tires and rims fitted to an axle shall not be less than the GAWR specified on the certification label.